



WINCH MODEL LARGE 22/2000

All rights reserved. No parts of this work may be reproduced in any form or by any means - graphic, electronic, or mechanical, including photocopying, recording, taping, or information storage and retrieval systems - without the written permission of the publisher.

Products that are referred to in this document may be either trademarks and/or registered trademarks of the respective owners. The publisher and the author make no claim to these trademarks.

While every precaution has been taken in the preparation of this document, the publisher and the author assume no responsibility for errors or omissions, or for damages resulting from the use of information contained in this document or from the use of hardware, programs or source code that may accompany it. In no event shall the publisher and the author be liable for any loss of profit or any other commercial damage caused or alleged to have been caused directly or indirectly by this document.

SPECIFICATION

Construction	All welded in corrosion resistant aluminium, frame and cable drum
Overall dimensions	Width: 2160 mm Height: 1800 mm Length: 1450 mm
Drum dimensions	Core length: 1330 mm Core diameter: 700 mm Flange diameter: 1300 mm

Cable capacity	2000 meter of 22,7 mm cable
Weight	670 kg. excl. Cable
Cable pull	Inner layer 3335 N - theoretical Outer layer 1790 N - theoretical
Cable speed	Inner layer, 39 m/min. Outer layer, 72 m./min.
Spooling system	Stainless steel shaft, belt driven with release mechanism. Cable dia. adjustable from 1 mm to 25 mm in 50 steps.
Electric motor	3000W. 3 ph, 1420 o/min.
Electric input	Three phase 230 V AC 50 Hz. 16 A
Controls	Frequency inverter, Manual control with 10 meters cable. Up, down and emergency stop. Potentiometer speed control.
Slip ring	Electric and optical slip ring from Focal Technologies (176-series)
Brake	Automatic
Temperature rating	-15° C to + 65° C

SPERRE AS

Telemark Teknologipark, Merdeveien 1, 3676 Notodden, Norway

E-mail: post@sperre-as.com, Phone: +47 35 02 50 00

<http://www.sperre-as.com>